

106 Push On

INDUSTRIAL
AUTOMATION

GREASING

PUSH ON

GAS

FUEL

CHEMICALS

WATER

Thermoplastic constant pressure hose for low pressure air and water line
Up to 20 bar (290 psi)



FEATURES

Inner Tube

Polyurethane

Reinforcement

One braid of synthetic fiber

Cover

Polyurethane, black,
white ink-jet branding

Applications

- Low pressure air and water line
- Free of paint affecting substances
- LABS free

Features

- Polyurethane tube and cover for high flexing giving long service life
- Antiabrasion cover for optimum wear resistance
- Push on fitting assembly without crimping

Description

Low pressure air and water line suitable for high flexing applications.
Available Black as standard, also available in Blue, Red, Green and Yellow.

Temperature Range

-40°C to +80°C
(-40°F to +176°F)

APPLICATIONS



PACKAGING



MULTICOLOR



Part No.	Hose size		ID		OD		WP		BP		Safety factor	Bend radius		Weight		Ferrule part no.		
	dash	inch	DN	mm	inch	mm	inch	bar	psi	bar		psi	mm	inch	g/m	lbs/ft	carbon	stainless
1062	-4	1/4"	6	6,30	0,248	11,20	0,441	20	290	80	1160	4:1	30	1,181	75	0,050		
1064	-6	3/8"	10	9,50	0,374	15,00	0,591	20	290	80	1160	4:1	50	1,969	115	0,077		No ferrule needed.
1065	-8	1/2"	12	12,70	0,500	19,10	0,752	20	290	80	1160	4:1	70	2,756	170	0,114		For more info check dedicated section at pages 187-189
1066	-10	5/8"	16	16,20	0,638	23,00	0,906	20	290	80	1160	4:1	90	3,543	220	0,148		
1067	-12	3/4"	20	19,00	0,748	26,00	1,024	20	290	80	1160	4:1	110	4,331	265	0,178		