

ABRA 10 SLURRY



MINING & QUARRIES

Abrasive materials hydraulic and pneumatic handling



APPLICATIONS

Hydraulic suction and discharge of abrasive products.

COUPLING/FITTINGS

Special half shelves coupling.

TECHNICAL DESCRIPTION

Inner tube	wear resistant NR, black, smooth.
Reinforcement	synthetic textile with embedded steel helix
Cover	wear resistant NR/SBR, black, smooth fabric impression.
Temperature range	-30°C => +70°C
Electrical Properties	conductive tube, R<1M0hm/m.

ORG

ABRA 10 SLURRY



TRELLEBORG

ABRA 10 SLURRY



50-200mm

ORG

ABRA 5 SLURRY



TRELLEBORG

ABRA 5 SLURRY



250-400mm



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
50.0	70.0	10	30	250	3.00	20	5513746
75.0	96.0	10	30	375	4.00	20	5513747
100.0	123.0	10	30	500	6.00	20	5513748
125.0	150.0	10	30	650	7.50	20	5513749
150.0	174.0	10	30	900	8.00	20	5513750
200.0	230.0	10	30	1400	12.00	10	5513751
250.0	282.0	5	15	1750	17.00	10	5513752
300.0	336.0	5	15	2100	22.00	10	5513753
350.0	386.0	5	15	2750	26.00	10	5513754
400.0	436.0	5	15	3500	30.00	10	5513755

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

