



AG 2100 MARINE CORRUGATED



MARINE EQUIPMENT



Boat equipment/Exhaust gas

APPLICATIONS

Marine engine wet exhaust systems where the exhaust gases are mixed with the discharge of cooling water.

ADVANTAGES

- Extreme flexibility.
- Low weight.
- Weather and ageing resistant.
- Corrugated and user friendly.
- DNV approved.

COUPLING/FITTINGS


Clamps.

COMPLEMENTARY INFORMATION

Certified by DNV in accordance to ISO 13363 type 2, SAE J 2006 type R2, Nordic Boat Standard MC9.
Other dimensions available on request.

TECHNICAL DESCRIPTION

Inner tube	CR, black, smooth.
Reinforcement	synthetic textile with steel wire embedded helix
Cover	CR, black, fabric impression, corrugated.
Temperature range	-30°C => +100°C, -30 Can intermittent withstand +580°C



and embossed: TRELLEBORG -? AG 2100 - ?MARINE WET EXHAUST -? SAE J2006R2 - ?ISO 13363:2004 – Type 2B (580°C) -? MC9 - ?ID - ?month/year - batch number

**MARINE EQUIPMENT****AG 2100 MARINE CORRUGATED**

ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
76.0	86.0	5	15	175	1.81	20	5500796
76.0	86.0	5	15	175	1.81	40	0071151
90.0	100.0	5	15	200	2.16	20	0071152
90.0	100.0	5	15	200	2.16	40	5500797
102.0	112.0	5	15	220	2.42	20	0071153
102.0	112.0	5	15	220	2.42	40	5500798
127.0	138.0	4	12	250	2.97	20	0071154
127.0	138.0	4	12	250	2.97	40	5500799
152.0	163.0	4	12	350	3.52	20	0071155
205.0	217.0	4	12	590	6.00	20	5014028

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

