

ALTIPLUS



AGRICULTURE

Farm/Spraying



APPLICATIONS

High pressure agricultural spraying (fungicide, weed killers, insecticides, etc.).

Also suitable for paint spraying and disinfection of buildings or high pressure water discharge.

ADVANTAGES

- A high performance hose for extra heavy duty service.
- Excellent coupling retention.
- A wide range of diameters.
- Non-marking cover.
- Good ageing and weather resistance.

COMPLEMENTARY INFORMATION

50% of the volume in each delivery will be random lengths, shortest length of 10m, at least 50% will be in fixed length mentioned in the table.


TECHNICAL DESCRIPTION

Inner tube	SBR, black, smooth.
Reinforcement	synthetic textile
Cover	SBR, beige, with two groups of three ribs.
Temperature range	-30°C => +70°C

STANDARD/APPROVAL

EN ISO 1401, type C for ID<16mm, type B for ID?16mm.

ISO





AGRICULTURE

ALTIPLUS



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
8.0	16.0	60	240	40	0.24	160	5501372
9.0	17.5	60	240	40	0.28	40	5501373
10.0	18.5	60	240	45	0.29	160	5501376
10.0	18.5	60	240	45	0.29	200	5501377
12.5	21.0	60	240	50	0.31	40	5501378
12.5	21.0	60	240	50	0.31	80	5501379
12.5	21.0	60	240	50	0.31	160	5501380
16.0	26.5	40	160	80	0.53	40	5501381
16.0	26.5	40	160	80	0.53	120	5501382
19.0	31.0	40.0	160.0	90	0.67	40	5501383
19.0	31.0	40.0	160.0	90	0.67	120	5501384
25.0	37.0	40.0	160.0	100	0.81	40	5501385
25.0	37.0	40.0	160.0	100	0.81	80	5501386

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

