

# AQUA 10 HOT SD



**GENERAL INDUSTRY**

Water/Suction applications



## APPLICATIONS

Hot water suction and delivery hose used in industry, construction and agricultural applications.

## TECHNICAL DESCRIPTION

Inner tube	high temperature resistant EPDM, black, smooth.
Reinforcement	synthetic textile with embedded steel helix
Cover	high temperature resistant EPDM, black, fabric impression.
Temperature range	-30°C => +100°C

**HOT SD**



**TRELLEBORG**

**AQUA 10 HOT SD**





GENERAL INDUSTRY

AQUA 10 HOT SD



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
38.0	48.0	10	30	160	1.01	40	5503660
51.0	63.0	10	30	200	1.57	40	5503661
63.0	75.0	10	30	245	2.21	20	59007847
63.0	75.0	10	30	245	2.21	40	5503662
76.0	88.0	10	30	320	2.43	20	59007848
76.0	88.0	10	30	320	2.43	40	5503663
102.0	116.0	10	30	410	3.73	20	59007849
102.0	116.0	10	30	410	3.73	40	5503654
127.0	143.0	10	30	510	5.82	20	59007850
127.0	143.0	10	30	510	5.82	40	5503655
152.0	169.0	10	30	610	8.25	20	59007851
152.0	169.0	10	30	610	8.25	40	5503656
203.0	225.0	10	30	1000	12.43	40	5503657
254.0	278.0	10	30	1270	17.39	40	5503720

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

