



CANALKLER 250 S ASSEMBLY



**CONSTRUCTION &
INFRASTRUCTURE**



Drain and sewer cleaning

APPLICATIONS

Sewer jetting and heavy duty, high pressure water cleaning.

ADVANTAGES

- Very low sliding resistance which allows: higher cleaning efficiency, reduction of cleaning time and therefore, reduction of fuel consumption.
- Longer lifespan thanks to the special cover compound with higher abrasion resistance.
- Better flexibility, even at low temperatures.
- Easy to handle and user friendly.
- Deformation resistance.
- Extra high strength and security due to aramide reinforcement.

COUPLING/FITTINGS


All hoses are assembled with BSP female/BSP male.
All assembled hoses are pressure tested at 375bar and have an unique hose number.

COMPLEMENTARY INFORMATION

Delivered with test certificate on each factory assembled hose.

TECHNICAL DESCRIPTION

Inner tube	SBR, black, smooth.
Reinforcement	aramide textile, braided
Cover	SBR/NR, black, smooth. Very low sliding resistance.
Temperature range	-30°C => +80°C



Embossed branding



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
13.0	25.6	250	625	70	0.45	40	5014178
13.0	25.6	250	625	70	0.45	60	5014179
13.0	25.6	250	625	70	0.45	80	5014180
13.0	25.6	250	625	70	0.45	100	5014916
13.0	25.6	250	625	70	0.45	120	5014005
19.0	31.6	250	625	90	0.61	40	5014181
19.0	31.6	250	625	90	0.61	80	5014182
19.0	31.6	250	625	90	0.61	100	5014459
19.0	31.6	250	625	90	0.61	120	5014006
25.0	39.3	250	625	100	0.90	40	5014183
25.0	39.3	250	625	100	0.90	50	5014874
25.0	39.3	250	625	100	0.90	80	5014184
25.0	39.3	250	625	100	0.90	100	5014238
25.0	39.3	250	625	100	0.90	120	5014007
25.0	39.3	250	625	100	0.90	150	5014461
25.0	39.3	250	625	100	0.90	160	5014185
25.0	39.3	250	625	100	0.90	180	5014186
25.0	39.3	250	625	100	0.90	200	5014520
25.0	39.3	250	625	100	0.90	240	5014733
32.0	47.6	250	625	130	1.12	40	5014187
32.0	47.6	250	625	130	1.12	80	5014188
32.0	47.6	250	625	130	1.12	120	5014008
32.0	47.6	250	625	130	1.12	150	5014466
32.0	47.6	250	625	130	1.12	160	5014189
32.0	47.6	250	625	130	1.12	180	5014190
32.0	47.6	250	625	130	1.12	200	5014655
38.0	54.0	250	500	155	1.35	120	5014009

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

