

COLORADO S



GENERAL INDUSTRY

DISCHARGE HOSES



APPLICATIONS

Water discharge for all types of industrial and agricultural medium pressure applications in harsh environments.

ADVANTAGES

Extremely resistant to ageing and atmospheric conditions.
 Coils flat for easy storage and handling.
 A robust construction to resist impact, kinking and abrasion.
 For fluids up to 100°C.
 Wide range of diameters.

TECHNICAL DESCRIPTION

Inner tube	EPDM, white, smooth.
Reinforcement	synthetic textile
Cover	EPDM, orange, fabric impression.
Temperature range	-30°C => +100°C

STANDARD/APPROVAL

In compliance with ISO 1403 type 1 (except branding).

ISO


COLORADO S

Made in France



TRELLEBORG

COLORADO S





GENERAL INDUSTRY

COLORADO S



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
40.0	49.0	10	28	320	0.91	20	0062298
40.0	49.0	10	28	320	0.91	40	0062297
45.0	54.0	10	28	360	1.01	20	0062303
45.0	54.0	10	28	360	1.01	40	0062302
50.0	60.0	10	28	500	1.26	20	0062308
50.0	60.0	10	28	500	1.26	40	0062307
60.0	70.0	10	28	600	1.51	20	0062318
60.0	70.0	10	28	600	1.51	40	0062317
65.0	76.5	10	28	650	1.80	20	0200059
65.0	76.5	10	28	650	1.80	40	0200060
70.0	81.5	10	28	700	2.01	20	0062328
75.0	86.5	10	28	750	2.15	20	0200061
75.0	86.5	10	28	750	2.15	40	0200062
80.0	92.0	10	28	850	2.43	20	0062336
80.0	92.0	10	28	850	2.43	40	0062337
89.0	101.0	10	28	900	2.71	20	0062339
100.0	112.0	10	28	1000	3.00	20	0062341
120.0	131.5	5	13	1200	3.41	10	0200006

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

