



# KLENET



## FOOD & BEVERAGE



Food industry/Cleaning

### APPLICATIONS

Washdown and cleaning in food processing industries, canneries, dairies, slaughterhouses, etc.

### ADVANTAGES

- Very good resistance to high temperatures.
- Smooth for easy handling with light-coloured, non-marking cover.
- Excellent resistance of the cover compound to animal and vegetable grease.
- Contains no phthalate.

### COUPLING/FITTINGS

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

### COMPLEMENTARY INFORMATION

Not recommended with washdown guns.

### TECHNICAL DESCRIPTION

Inner tube	food grade quality oil resistant NBR, white, smooth.
Reinforcement	synthetic textile
Cover	oil and weather resistant NBR/PVC, blue, smooth.
Temperature range	-20°C => +95°C

### STANDARD/APPROVAL

EU regulations No. 1935/2004, 2023/2006.

EU

FDA regulation No. 21 CFR 177.2600.

FDA


French legislation.

RF

German legislation: BfR recommendation XXI cat. 2.

BfR

All relevant migrations tests (France and FDA) were performed by the French institute of Poitiers (IANESCO) and confirmed compliant.



and embossed: week/year - batch number

**FOOD & BEVERAGE****KLENET**

ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
13.0	21.4	10	30	80	0.30	20	0060962
13.0	21.4	10	30	80	0.30	40	0060961
13.0	21.4	10	30	80	0.30	60	0060952
13.0	21.4	10	30	80	0.30	120	0060953
16.0	25.0	10	30	95	0.38	20	0060964
16.0	25.0	10	30	95	0.38	40	0060963
16.0	25.0	10	30	95	0.38	60	0060954
16.0	25.0	10	30	95	0.38	120	0060955
19.0	28.4	10	30	115	0.48	20	0060966
19.0	28.4	10	30	115	0.48	40	0060965
19.0	28.4	10	30	115	0.48	60	0060956
25.0	35.0	10	30	155	0.62	20	0060968
25.0	35.0	10	30	155	0.62	40	0060967
25.0	35.0	10	30	155	0.62	60	0060957

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

