

# MULTI 10 OIL



## GENERAL INDUSTRY



Multipurpose oil

### APPLICATIONS

Versatile hose for diesel, mineral oil and grease with aromatic content <50%.

### TECHNICAL DESCRIPTION

---

Inner tube: NBR, black, smooth.

---

Reinforcement: synthetic textile.

---

Cover: NBR, black, smooth.

---

Temperature range: -30°C to +100°C.

---

Electrical properties: conductive tube and cover,  $R \leq 1M\Omega/lg$  ( $R \leq 10^6 \Omega/lg$ ).

---



GENERAL INDUSTRY

MULTI 10 OIL



ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK ( ) or min. order m
6.0	12.0	10	40	45	0.13	40	5513845	
8.0	14.0	10	40	55	0.14	40	5513846	
10.0	17.0	10	40	60	0.21	40	5513847	
13.0	20.0	10	40	80	0.26	40	5513848	
16.0	24.0	10	40	100	0.34	40	5513849	
19.0	27.0	10	40	120	0.41	40	5513850	
25.0	34.0	10	40	150	0.6	40	5513851	

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).



TRELLEBORG

[WWW.TRELLEBORG.COM/FLUIDHANDLING](http://WWW.TRELLEBORG.COM/FLUIDHANDLING)