

# MULTI 25 OIL



**GENERAL INDUSTRY**

Multipurpose oil



## APPLICATIONS

Versatile hose for diesel, mineral oil and grease with aromatic content <50%.

## TECHNICAL DESCRIPTION

Inner tube	NBR, black, smooth.
Reinforcement	synthetic textile
Cover	NBR, black, smooth.
Temperature range	-30°C => +100°C
Electrical Properties	conductive tube and cover, R≤1MΩ/1g (R≤10 <sup>6</sup> Ω/1g).





GENERAL INDUSTRY

MULTI 25 OIL



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
6.0	13.0	25	80	40	0.14	40	5513852
8.0	15.0	25	80	50	0.17	40	5513853
10.0	17.0	25	80	60	0.19	40	5513854
13.0	21.0	25	80	80	0.28	40	5513855
16.0	25.0	25	80	100	0.33	40	5513856
19.0	28.0	25	80	120	0.43	40	5513857
25.0	35.0	25	80	150	0.61	40	5513858

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

