

OIL 20 D



OIL & GAS

Oil and petroleum/Oil cargo



APPLICATIONS

Delivery hose for general applications of mineral and synthetic oils with aromatic content up to 50%, mainly for oil platforms, marine fueling, storage tanks or other industrial facilities. Limited use for biofuels. Consult us.

ADVANTAGES

Weather, flame, oil projection, UV and ozone resistant. Up to 60m long.

TECHNICAL DESCRIPTION

Inner tube	NBR, black, smooth.
Reinforcement	synthetic textile
Cover	CR, black, fabric impression.
Temperature range	-30°C => +85°C
Electrical Properties	crossing antistatic wires and conductive tube, $R < 10^6 \Omega / \text{lg}$.



and embossed: TRELLEBORG - OIL 20 D - ND - WP 20 bar - ? - month/year - batch number



OIL & GAS

OIL 20 D



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
102.0	118.0	20	60	815	3.77	60	59011978
152.0	172.0	20	60	1520	7.12	60	59011980
203.0	235.0	20	60	2030	15.19	40	59013044
254.0	292.0	20	60	2540	23.28	20	59013045

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

