

PLUTON RED



GENERAL INDUSTRY

Welding hoses



APPLICATIONS

Rubber hose for acetylene supply in welding application.

ADVANTAGES

Flexible and light weight for easy handling.

Long, safe service life.

The cover is particularly resistant to atmospheric conditions (ozone and hot spots).

Flame resistant in case of flashback.

Very strong textile reinforcement giving high safety factor.

Clear branding showing gas symbol and date of manufacture.


TECHNICAL DESCRIPTION

Inner tube	SBR/NR, black, smooth.
Reinforcement	synthetic textile
Cover	EPDM, red, smooth.
Temperature range	-30°C => +80°C

STANDARD/APPROVAL

ISO 3821.

ISO





GENERAL INDUSTRY

PLUTON 20 RED



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
5.0	11.0	20	60	50	0.12	20	0200549
5.0	11.0	20	60	50	0.12	40	0200550
6.3	12.0	20	60	55	0.13	20	0200032
6.3	12.0	20	60	55	0.13	40	0200031
6.3	12.0	20	60	55	0.13	100	0200030
6.3	12.0	20	60	55	0.13	120	0200029
8.0	14.0	20	60	65	0.16	20	0200036
8.0	14.0	20	60	65	0.16	40	0200035
8.0	14.0	20	60	65	0.16	100	0200034
8.0	14.0	20	60	65	0.16	120	0200033
10.0	17.0	20	60	75	0.23	20	0060180
10.0	17.0	20	60	75	0.23	40	0060179
10.0	17.0	20	60	75	0.23	100	0200038
10.0	17.0	20	60	75	0.23	120	0060178
20.0	27.5	20	60	90	0.38	40	5503044

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

