

# PROJECTOR 40



## CONSTRUCTION & INFRASTRUCTURE

Spraying



### APPLICATIONS

For spraying of mortar and mixed concrete as well as dry products.  
Used as a service hose between pump and nozzle in transporting plaster, grout and ready mixed concrete.

### ADVANTAGES

Light weight, flexible and is easy to handle.  
Abrasion resistant tube compound.  
Conductive inner tube compound gives increased safety for the operator.  
Non-staining white cover avoids traces on walls and floors.


### TECHNICAL DESCRIPTION

|                       |   |
|-----------------------|---|
| Inner tube            | wear resistant NR, black, smooth.                                     |
| Reinforcement         | synthetic textile   |
| Cover                 | wear and weather resistant SBR, black, fabric impression.             |
| Temperature range     | -30°C => +70°C  |
| Electrical Properties | conductive tube, $R < 2 \cdot 10^6 \Omega/m$ .                        |
| Special Properties    | abrasion resistance of tube <40mm <sup>3</sup> according to ISO 4649. |



TRELLEBORG

**PROJECTOR 40** WP 12 BAR





| ID (MM) | OD (MM) | WORKING PRESSURE (BAR) | BURSTING PRESSURE (BAR) | BENDING RADIUS (MM) | WEIGHT (KG/M) | LENGTH (M) | ARTICLE NUMBER |
|---------|---------|------------------------|-------------------------|---------------------|---------------|------------|----------------|
| 25.0    | 44.0    | 12                     | 40                      | 120                 | 1.20          | 40         | 59006811       |
| 32.0    | 52.0    | 12                     | 40                      | 150                 | 1.57          | 40         | 59006812       |
| 40.0    | 60.0    | 12                     | 40                      | 180                 | 1.80          | 20         | 59006813       |
| 40.0    | 60.0    | 12                     | 40                      | 180                 | 1.80          | 40         | 59006814       |
| 50.0    | 70.0    | 12                     | 40                      | 250                 | 2.22          | 20         | 59006815       |
| 50.0    | 70.0    | 12                     | 40                      | 250                 | 2.22          | 40         | 59006816       |
| 60.0    | 80.0    | 12                     | 40                      | 290                 | 2.30          | 20         | 59006817       |
| 60.0    | 80.0    | 12                     | 40                      | 290                 | 2.30          | 40         | 59006818       |
| 63.0    | 90.0    | 12                     | 40                      | 340                 | 2.83          | 20         | 59006949       |
| 65.0    | 85.0    | 12                     | 40                      | 320                 | 2.70          | 20         | 59006819       |
| 65.0    | 85.0    | 12                     | 40                      | 320                 | 2.70          | 40         | 59006820       |

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

