

# STARKLER



## GENERAL INDUSTRY

Hot water and multipurpose chemicals



### APPLICATIONS

A versatile hose for high pressure cleaning operations and general discharge service using hot or cold water and many other fluids (see chemical resistance table for EPDM). Suitable for all sectors: building and public works, industry, agriculture, etc.

### ADVANTAGES

- Extremely resistant to ageing and atmospheric conditions.
- Wide range of operating temperatures (-30°C to +100°C).
- Wide range of diameters.
- Excellent mechanical properties.
- Resistant to many fluids.
- Attractive, well-finished appearance.
- Long service life.

### TECHNICAL DESCRIPTION

Inner tube	EPDM, black, smooth.
Reinforcement	synthetic textile
Cover	EPDM, black, smooth for ID from 12.7 to 25.4mm, fabric impression for ID from 30 to 38mm.
Temperature range	-30°C => +100°C

### STANDARD/APPROVAL

In compliance with ISO 1403 type 2 (except branding).



and in opposite:



12.7-25.4mm



30-38mm



GENERAL INDUSTRY

STARKLER



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
12.7	20.7	20	60	55	0.27	40	0060013
12.7	20.7	20	60	55	0.27	80	0060990
15.8	24.0	20	60	70	0.33	20	0060014
15.8	24.0	20	60	70	0.33	40	0060015
15.8	24.0	20	60	70	0.33	80	0060991
25.4	35.0	20	60	100	0.58	20	0060018
25.4	35.0	20	60	100	0.58	40	0060019
25.4	35.0	20	60	100	0.58	80	0060993
30.0	39.0	10	30	240	0.72	20	0200259
30.0	39.0	10	30	240	0.72	40	0200260
32.0	41.0	10	30	260	0.77	20	0123234
32.0	41.0	10	30	260	0.77	40	0123239
35.0	44.0	10	30	280	0.83	20	0200261
35.0	44.0	10	30	280	0.83	40	0200262
38.0	47.0	10	30	310	0.89	20	0123245
38.0	47.0	10	30	310	0.89	40	0070387

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

