

STEAM 16 RED



OIL & GAS

Steam



APPLICATIONS

High pressure steam hose.

TECHNICAL DESCRIPTION

Inner tube	synthetic EPDM rubber, black, smooth.
Reinforcement	steel braid
Cover	synthetic EPDM rubber, red, fabric impression.
Temperature range	-30°C => +210°C
Electrical Properties	R<1MΩ/1g.

STANDARD/APPROVAL

BS 5342:1985 type 2 class A.

BS



TRELLEBORG

STEAM 16 RED - BS5342:1985 - 2A - 16 BAR - ND - month/year



13-25mm:



TRELLEBORG

STEAM 16 RED - BS5342:1985 - 2A - 16 BAR - ND - month/year



32-51mm:



OIL & GAS

STEAM 16 RED



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
13.0	24.0	16	160	150	0.51	40	5513659
16.0	28.0	16	160	190	0.64	40	5513660
19.0	32.0	16	160	230	0.80	40	5513661
19.0	32.0	16	160	230	0.80	60	5514008
25.0	38.0	16	160	300	1.00	40	5513662
25.0	38.0	16	160	300	1.00	60	5514009
32.0	48.0	16	160	320	1.44	40	5513663
38.0	54.0	16	160	380	1.75	40	5513664

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

