

STEAM 16



OIL & GAS

Steam



APPLICATIONS

High pressure steam hose.

TECHNICAL DESCRIPTION


| | |
|-----------------------|--|
| Inner tube | synthetic EPDM rubber, black, smooth. |
| Reinforcement | steel braid |
| Cover | synthetic EPDM rubber, black, fabric impression. |
| Temperature range | -30°C => +210°C |
| Electrical Properties | R<1MΩ/1g. |

STANDARD/APPROVAL


BS 5342:1985 type 2 class A.

BS

EN



32-51mm :



13-25mm:



OIL & GAS

STEAM 16



| ID (MM) | OD (MM) | WORKING PRESSURE (BAR) | BURSTING PRESSURE (BAR) | BENDING RADIUS (MM) | WEIGHT (KG/M) | LENGTH (M) | ARTICLE NUMBER |
|---------|---------|------------------------|-------------------------|---------------------|---------------|------------|----------------|
| 13.0 | 24.0 | 16 | 160 | 150 | 0.47 | 40 | 5513652 |
| 16.0 | 28.0 | 16 | 160 | 190 | 0.59 | 40 | 5513653 |
| 19.0 | 32.0 | 16 | 160 | 230 | 0.73 | 40 | 5513654 |
| 25.0 | 38.0 | 16 | 160 | 300 | 0.93 | 40 | 5513655 |
| 32.0 | 48.0 | 16 | 160 | 380 | 1.44 | 40 | 5513656 |
| 38.0 | 54.0 | 16 | 160 | 380 | 1.75 | 40 | 5513657 |
| 51.0 | 69.0 | 16 | 160 | 500 | 2.31 | 40 | 5513658 |

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

