

# STEAM 6



**OIL & GAS**

Steam



## APPLICATIONS

Low pressure steam hose.

## TECHNICAL DESCRIPTION

Inner tube	synthetic EPDM rubber, black, smooth.
Reinforcement	synthetic textile
Cover	synthetic EPDM rubber, black, fabric impression.
Temperature range	-30°C => +164°C
Electrical Properties	R<1MΩ/ig.

## STANDARD/APPROVAL

EN ISO 6134:2017 type 1 class A.

ISO



TRELLEBORG

**STEAM 6 - EN ISO 6134:2017 - 1A - STEAM - 6 BAR (0.6MPa) - 164°C - ND - Ω - 1Q-20**





OIL & GAS

STEAM 6



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
19.0	33.0	6	60	190	0.69	40	5513647
25.0	40.0	6	60	250	0.96	40	5513648
32.0	48.0	6	60	320	1.26	40	5513649
38.0	54.0	6	60	380	1.45	40	5513650
51.0	69.0	6	60	500	1.86	40	5513651

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

