

TRELLVAC Extractor HD



MINING & QUARRIES

Evacuation and material handling hoses



APPLICATIONS

Universal material handling hose for suction of shavings, sand, dust and powder, etc.

Applications include sawmills, chip board and wood veneer plants, fiberboard plants, etc.

ADVANTAGES

- Light and flexible design with steel helix.
- Good bending radius.
- Especially useful when low weight and easy handling in combination with good abrasion resistance are valued.

COMPLEMENTARY INFORMATION

OD measured on top of corrugation.

Can be used in ATEX zones.

TECHNICAL DESCRIPTION

Inner tube	wear resistant SBR/NR, black, smooth.
Reinforcement	synthetic textile with embedded steel helix
Cover	wear and weather resistant SBR/NR, black, corrugated.
Temperature range	-40°C => +90°C
Electrical Properties	conductive tube and cover, $R < 10^6 \Omega/m$.





MINING & QUARRIES

TRELLVAC EXTRACTOR HD



ID (MM)	OD (MM)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
38.0	47.0	50	0.73	12	0124823
51.0	60.0	75	0.96	12	0129711
63.0	72.0	100	1.13	12	0124849
76.0	85.0	120	1.37	12	0124825
102.0	111.0	150	1.85	12	0125779
127.0	136.0	175	2.33	12	0124828
152.0	161.0	200	2.77	12	0124829

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

