

# TRUCK 7



## BULK MATERIALS HANDLING

Bulk tank truck discharge




### APPLICATIONS

Delivery hose to transfer abrasive material such as cement, sand, etc.

### TECHNICAL DESCRIPTION

Inner tube	natural rubber, black, smooth.
Reinforcement	synthetic textile and antistatic wire
Cover	synthetic SBR rubber, black, fabric impression.
Temperature range	-30°C => +80°C
Electrical Properties	Conductive tube. ATEX and TRGS 727 approval for hazardous areas.





ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
75.0	93.0	7	21	2.77	40	5513666
90.0	101.0	7	21	2.00	40	5513795
90.0	106.0	7	21	2.89	40	5513667
100.0	120.0	7	21	4.08	40	5513668
102.0	119.0	7	21	3.00	40	5513713
102.0	122.0	7	21	4.00	40	5513714
110.0	123.0	7	21	3.00	40	5513796
127.0	145.0	7	21	4.49	40	5513669
152.0	172.0	7	21	5.61	40	5513670

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

