

# VOLUKLER GREEN



## OIL & GAS

Oil and petroleum/Petrol pumps



### APPLICATIONS

For equipment of petrol pumps: regular, super and unleaded petrol, biofuel, diesel fuel.

### ADVANTAGES

Good resistance to ageing and abrasion from repeated dragging over oily floors.

Complies with European standard.

Can be supplied with end fittings.


### TECHNICAL DESCRIPTION

Inner tube	petrol resistant NBR, black, smooth.
Reinforcement	synthetic textilebraided
Cover	oil and weather resistant NBR/PVC, green, smooth.
Temperature range	-25°C => +65°C
Electrical Properties	conductive tube, $R < 10^6 \Omega / \text{lg}$ .

### STANDARD/APPROVAL

EN 1360:2013 type 1.

EN





OIL & GAS

VOLUKLER VERT



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
16.0	25.0	16	48	80	0.37	40	5513451
16.0	25.0	16	48	80	0.37	80	5513452

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

