

VOLUKLER



OIL & GAS

Oil and petroleum/Petrol pumps



APPLICATIONS

For equipment of petrol pumps: regular, super and unleaded petrol, biofuel, diesel fuel.

ADVANTAGES

Good resistance to ageing and abrasion from repeated dragging over oily floors.
Complies with European standard.
Can be supplied ready fitted and tested with end fittings.

COMPLEMENTARY INFORMATION

Blue, red or green cover upon request.

TECHNICAL DESCRIPTION

Inner tube	petrol resistant NBR, black, smooth.
Reinforcement	synthetic textilebraided
Cover	oil and weather resistant NBR/ PVC, black, smooth.
Temperature range	-30°C => +55°C
Electrical Properties	conductive tube, R<10 ⁶ Ω/1g.

STANDARD/APPROVAL

ID 21mm: also available as VOLUKLER VR ASSEMBLY with internal vapour recovery tube for petrol dispensing systems, compliant with EN 13483:2013/1, consult us.


EN

TRELLEBORG - VOLUKLER - EN 1360:2013 - TYPE 1 - ND - 16 BAR - Ω - quarter/year - batch number - Made in France



16-19-25mm

TRELLEBORG - VOLUKLER - EN 1360:2013 - EN 13483:2013 - TYPE 1 - ND - 16 BAR - Ω - quarter/year - batch number - Made in France



21mm



OIL & GAS

VOLUKLER



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
16.0	25.0	16	48	80	0.40	40	5513438
16.0	25.0	16	48	80	0.40	80	5513439
16.0	25.0	16	48	80	0.40	120	5513440
19.0	31.0	16	48	100	0.63	40	5513442
19.0	31.0	16	48	100	0.63	80	5513443
19.0	31.0	16	48	100	0.63	120	5513444
21.0	31.0	16	48	75	0.55	40	5513466
21.0	31.0	16	48	75	0.55	80	5513467
25.0	37.0	16	48	140	0.75	40	5513446
25.0	37.0	16	48	140	0.75	80	5513447

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

