

# VULPANE



## GENERAL INDUSTRY

Welding hoses



### APPLICATIONS

Rubber hose for LPG (gas cylinders, heaters, welding and LPG lines).

### ADVANTAGES

Flexible and light weight for easy handling.

Long, safe service life.

A hose cover particularly resistant to atmospheric conditions (ozone and hot spots).

Special, high quality rubber compounds.

Very strong textile reinforcement giving high safety factor.

Clear branding showing gas symbol and date of manufacture.


### TECHNICAL DESCRIPTION

|                   |                         |
|-------------------|-------------------------|
| Inner tube        | NBR/SBR, black, smooth. |
| Reinforcement     | synthetic textile       |
| Cover             | EPDM, orange, smooth.   |
| Temperature range | -30°C => +80°C          |

### STANDARD/APPROVAL

ISO 3821.

ISO





GENERAL INDUSTRY

VULPANE



| ID (MM) | OD (MM) | WORKING PRESSURE (BAR) | BURSTING PRESSURE (BAR) | BENDING RADIUS (MM) | WEIGHT (KG/M) | LENGTH (M) | ARTICLE NUMBER |
|---------|---------|------------------------|-------------------------|---------------------|---------------|------------|----------------|
| 6.3     | 12.0    | 20                     | 60                      | 55                  | 0.12          | 20         | 0200010        |
| 6.3     | 12.0    | 20                     | 60                      | 55                  | 0.12          | 40         | 0200009        |
| 6.3     | 12.0    | 20                     | 60                      | 55                  | 0.12          | 100        | 5501202        |
| 6.3     | 12.0    | 20                     | 60                      | 55                  | 0.12          | 120        | 0200008        |
| 8.0     | 14.0    | 20                     | 60                      | 65                  | 0.15          | 40         | 0200012        |
| 8.0     | 14.0    | 20                     | 60                      | 65                  | 0.15          | 50         | 5012645        |
| 8.0     | 14.0    | 20                     | 60                      | 65                  | 0.15          | 60         | 5012708        |
| 8.0     | 14.0    | 20                     | 60                      | 65                  | 0.15          | 80         | 0129712        |
| 8.0     | 14.0    | 20                     | 60                      | 65                  | 0.15          | 100        | 5501203        |
| 8.0     | 14.0    | 20                     | 60                      | 65                  | 0.15          | 120        | 0200011        |
| 9.0     | 16.0    | 20                     | 60                      | 70                  | 0.18          | 20         | 0200551        |
| 9.0     | 16.0    | 20                     | 60                      | 70                  | 0.18          | 40         | 0200552        |
| 9.0     | 16.0    | 20                     | 60                      | 70                  | 0.18          | 120        | 0200553        |
| 10.0    | 17.0    | 20                     | 60                      | 75                  | 0.20          | 20         | 0200016        |
| 10.0    | 17.0    | 20                     | 60                      | 75                  | 0.20          | 25         | 5010110        |
| 10.0    | 17.0    | 20                     | 60                      | 75                  | 0.20          | 40         | 0200015        |
| 10.0    | 17.0    | 20                     | 60                      | 75                  | 0.20          | 100        | 5501204        |
| 10.0    | 17.0    | 20                     | 60                      | 75                  | 0.20          | 120        | 0200014        |
| 20.0    | 27.5    | 20                     | 60                      | 130                 | 0.37          | 40         | 5503077        |

Tolerance on length:  $\pm 1\%$  (ISO 1307 Standard).

