

ZEPHIR S



MINING & QUARRIES

Evacuation and material handling hoses



APPLICATIONS

For suction of light industrial debris and dust.
Suitable for conveying small particles and moderately abrasive materials.

ADVANTAGES

Very light weight and easy to handle.
Excellent bending radius and flexibility.
Very good crush resistance.

TECHNICAL DESCRIPTION

Inner tube	wear resistant NR, beige, smooth.
Cover	rubber coated fabric, white, corrugated.
Temperature range	-30°C => +70°C





ID (MM)	OD (MM)	BENDING RADIUS (MM)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
30.0	39.0	150	0.50	10	0126702
35.0	44.0	175	0.57	10	0123919
40.0	49.0	200	0.63	10	0074118
50.0	59.0	250	0.79	10	0201844
60.0	69.0	300	0.90	10	0201845
70.0	79.0	350	1.02	10	0074130
80.0	91.0	400	1.46	10	0201846
100.0	111.0	500	1.79	10	0201847
105.0	116.0	525	1.84	10	0070668
115.0	126.0	575	2.00	10	0070553
125.0	136.0	625	2.23	10	0095689
150.0	164.0	750	3.76	10	0202128

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

