

// 071AI

**LPG welding 12 bar (180 psi)
AS 1335****Tube:** black NBR.**Reinforcement:** high tensile textile cords.**Cover:** orange SBR/EPDM - abrasion and ozone resistant.**Application:** LPG welding.**Constant operation:** -25 °C +80 °C (-13 °F +176 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
5,0	3/16"	12,00	0,47	12	180	48	720	50,0	1,97		0,140	0,10	

// 071EH

**Oxygen/acetylene twin welding 12 bar (180 psi)
AS 1335****Tube:** black SBR.**Reinforcement:** high tensile textile cords.**Cover:** blue, red SBR/EPDM - abrasion and ozone resistant.**Application:** oxygen/acetylene twin welding.**Constant operation:** -25 °C +80 °C (-13 °F +176 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
5,0	3/16"	12,00	0,47	12	180	36	540	50,0			0,280	0,19	

// 071EI

**Oxygen/LPG twin welding 12 bar (180 psi)
AS 1335****Tube:** black SBR-NBR.**Reinforcement:** high tensile textile cords.**Cover:** blue, orange SBR/EPDM - abrasion and ozone resistant.**Application:** oxygen/LPG twin welding.**Constant operation:** -25 °C +80 °C (-13 °F +176 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
5,0	3/16"	12,00	0,47	12	180	48	720	50,0	1,97		0,280	0,19	