

// 151AA



Compressed air 20 bar (300 psi) - Heavy duty mining

Tube: black SBR/NBR - oil mist resistant.
Reinforcement: high tensile textile cords.
Cover: black SBR - abrasion and ozone resistant.
Application: compressed air designed for heavy duty mining applications.
Constant operation: -30 °C +80 °C (-22 °F +176 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
13,0	1/2"	23,00	0,91	20	300	60	900				0,420	0,29
19,0	3/4"	31,00	1,22	20	300	60	900				0,690	0,47
25,0	1"	37,00	1,46	20	300	60	900				0,860	0,58
38,0	1 1/2"	52,00	2,05	20	300	60	900				1,260	0,85
51,0	2"	67,00	2,64	20	300	60	900				2,190	1,48

// 151AK



Compressed air 20 bar (300 psi) - Heavy duty mining

Tube: black SBR/NBR - oil mist resistant.
Reinforcement: high tensile textile cords.
Cover: yellow SBR - abrasion and ozone resistant.
Application: compressed air designed for heavy duty mining applications.
Constant operation: -30 °C +80 °C (-22 °F +176 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
13,0	1/2"	23,00	0,91	20	300	60	900				0,420	0,29
19,0	3/4"	31,00	1,22	20	300	60	900				0,690	0,47
25,0	1"	37,00	1,46	20	300	60	900				0,860	0,58
38,0	1 1/2"	52,00	2,05	20	300	60	900				1,260	0,85
51,0	2"	67,00	2,64	20	300	60	900				2,200	1,48