

// 157AK

**Compressed air 27 bar (400 psi) - Heavy duty mining****Tube:** black SBR/NBR - oil mist resistant.**Reinforcement:** high tensile textile cords.**Cover:** yellow SBR - abrasion and ozone resistant.**Application:** compressed air designed for heavy duty mining applications.**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

												
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
19,0	3/4"	29,00	1,14	27	400	81	1200	190,0	7,48		0,550	0,37
25,0	1"	35,00	1,38	27	400	81	1200	250,0	9,84		0,700	0,48
32,0	1 1/4"	44,00	1,73	27	400	81	1200	320,0	12,60		0,920	0,62
38,0	1 1/2"	50,00	1,97	27	400	81	1200	380,0	14,96		1,050	0,71
51.0	2"	65.00	2.56	27	400	81	1200	510.0	20.08		1.690	1.14

// 189AK

**Air-water delivery - PVC - FRAS
AS 2660/A - AS/NZS - 2554/A****Tube:** black antistatic PVC.**Reinforcement:** high tensile textile cords.**Cover:** yellow ribbed PVC with longitudinal antistatic stripes - abrasion and ozone resistant.**Application:** compressed air in underground mining applications. Specially designed for roof bolting applications.**Constant operation:** -5 °C +60 °C (+23 °F +140 °F)

												
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
13,0	1/2"	21,00	0,83	20	300	70	1000	104,0	4,09		0,285	0,20
19,0	3/4"	29,00	1,14	20	300	70	1000	152,0	5,98		0,500	0,34
25,0	1"	35,00	1,38	35	525	70	1000	200,0	7,87		0,640	0,44
38,0	1 1/2"	48,00	1,89	20	300	70	1000	304,0	11,97		0,960	0,65
50,0	2"	63,00	2,48	20	300	70	1000	400,0	15,75		1,415	0,96