

Design and dimensions shown may be changed without prior notice

// 240AA

**Air-water delivery 20 bar (300 psi) - FRAS exceeds AS 2660/B****Tube:** black conductive SBR/NR.**Reinforcement:** high tensile textile cords.**Cover:** black conductive SBR - abrasion, ozone and fire resistant.**Application:** air, water and stone dust delivery in underground mines.**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft			
13,0	1/2"	23,00	0,91	20	300	80	1200	78,0	3,07		0,350	0,24			
19,0	3/4"	31,00	1,22	20	300	80	1200	114,0	4,49		0,520	0,35			
25,0	1"	37,00	1,46	20	300	80	1200	150,0	5,91		0,750	0,51			
32,0	1 1/4"	46,00	1,81	20	300	80	1200	192,0	7,56		1,000	0,68			
38,0	1 1/2"	52,00	2,05	20	300	80	1200	228,0	8,98		1,130	0,76			
51,0	2"	67,00	2,64	20	300	80	1200	306,0	12,05		1,600	1,08			
63,0	2 1/2"	79,00	3,11	20	300	80	1200	378,0	14,88		2,220	1,50			
76,0	3"	92,00	3,62	20	300	70	1000	456,0	17,95		2,620	1,77			
102,0	4"	118,00	4,65	20	300	70	1000	612,0	24,09		3,430	2,31			

// 241AA

**Air-water delivery 35 bar (525 psi) AS 2660/B****Tube:** black conductive SBR/NR.**Reinforcement:** high tensile textile cords.**Cover:** black conductive SBR - abrasion, ozone and fire resistant.**Application:** air, water and stone dust delivery in underground mines.**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft			
25,0	1"	37,00	1,46	35	525	85	1275	150,0	5,91		0,750	0,51			