

// 254AA



Air-water delivery 10 bar (150 psi)

Tube: black SBR.
Reinforcement: high tensile textile cords.
Cover: black SBR - abrasion and ozone resistant.
Application: air and water delivery.
Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↙		↘		⤴		⤵		⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
19,0	3/4"	27,00	1,06	10	150	30	450				0,400	0,27	
25,0	1"	33,00	1,30	10	150	30	450				0,540	0,37	
32,0	1 1/4"	42,00	1,65	10	150	30	450				0,830	0,56	
38,0	1 1/2"	48,00	1,89	10	150	30	450				0,980	0,66	
51,0	2"	61,00	2,40	10	150	30	450				1,290	0,87	
63,0	2 1/2"	75,00	2,95	10	150	30	450				1,920	1,30	
76,0	3"	88,00	3,46	10	150	30	450				2,310	1,56	
102,0	4"	114,00	4,49	10	150	30	450				3,120	2,10	
152,0	6"	166,00	6,54	10	150	30	450				4,690	3,16	
203,0	8"	219,00	8,62	10	150	20	300				6,950	4,68	

// 254AH



Air-water delivery 10 bar (150 psi)

Tube: black SBR.
Reinforcement: high tensile textile cords.
Cover: red SBR - abrasion and ozone resistant.
Application: air and water delivery.
Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↙		↘		⤴		⤵		⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
32,0	1 1/4"	42,00	1,65	10	150	30	450				0,830	0,56	
38,0	1 1/2"	48,00	1,89	10	150	30	450				0,970	0,66	
51,0	2"	61,00	2,40	10	150	30	450				1,290	0,87	

// 256AA



Water-irrigation 18 bar (270 psi) - Heavy duty

Tube: black EPDM.
Reinforcement: high tensile textile cords.
Cover: black EPDM - abrasion and ozone resistant.
Application: heavy duty water discharge.
 Specially designed for high pressure irrigation systems.
Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↙		↘		⤴		⤵		⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
51,0	2"	61,00	2,40	18	270	45	650				1,070	0,72	
60,0	2 3/8"	72,00	2,83	18	270	45	650				1,390	0,94	
70,0	2 3/4"	82,00	3,23	18	270	45	650				1,610	1,09	
76,0	3"	88,00	3,46	18	270	45	650				1,720	1,16	
80,0	3 1/8"	92,00	3,62	18	270	45	650				1,880	1,27	
90,0	3 1/2"	102,00	4,02	18	270	45	650				2,080	1,40	
102,0	4"	114,00	4,49	18	270	45	650				2,360	1,59	
120,0	4 3/4"	132,00	5,20	18	270	45	650				2,870	1,93	
152,0	6"	168,00	6,61	18	270	36	540				4,920	3,31	