

## // 264GL

**Water S&D - PVC - Light duty**

**Construction:** green transparent PVC - abrasion and ozone resistant.

**Reinforcement:** white shock resistant rigid PVC.

**Application:** water suction and delivery.

**Constant operation:** -5 °C +60 °C (+23 °F +140 °F)

| mm   | in     | mm | in | bar | psi | bar | psi | mm    | in    | %  | kg/m  | lb/ft |
|------|--------|----|----|-----|-----|-----|-----|-------|-------|----|-------|-------|
| 20,0 | 13/16" |    |    | 7   | 100 | 21  | 300 | 110,0 | 4,33  | 60 | 0,200 | 0,14  |
| 25,0 | 1"     |    |    | 7   | 100 | 21  | 300 | 138,0 | 5,43  | 60 | 0,250 | 0,17  |
| 32,0 | 1 1/4" |    |    | 6   | 90  | 18  | 270 | 176,0 | 6,93  | 60 | 0,340 | 0,23  |
| 38,0 | 1 1/2" |    |    | 5   | 75  | 15  | 225 | 209,0 | 8,23  | 60 | 0,440 | 0,30  |
| 51,0 | 2"     |    |    | 5   | 75  | 15  | 225 | 281,0 | 11,06 | 60 | 0,650 | 0,44  |

## // 266GL

**Water S&D - PVC - Standard duty**

**Construction:** green transparent PVC - abrasion and ozone resistant.

**Reinforcement:** white shock resistant rigid PVC.

**Application:** water suction and delivery.

**Constant operation:** -5 °C +60 °C (+23 °F +140 °F)

| mm    | in     | mm | in | bar | psi | bar | psi | mm    | in    | %  | kg/m  | lb/ft |
|-------|--------|----|----|-----|-----|-----|-----|-------|-------|----|-------|-------|
| 25,0  | 1"     |    |    | 7   | 100 | 21  | 300 | 113,0 | 4,45  | 70 | 0,290 | 0,20  |
| 32,0  | 1 1/4" |    |    | 6   | 90  | 18  | 270 | 144,0 | 5,67  | 70 | 0,390 | 0,27  |
| 38,0  | 1 1/2" |    |    | 5   | 75  | 15  | 225 | 171,0 | 6,73  | 70 | 0,510 | 0,35  |
| 45,0  | 1 3/4" |    |    | 5   | 75  | 15  | 225 | 203,0 | 7,99  | 70 | 0,670 | 0,46  |
| 51,0  | 2"     |    |    | 5   | 75  | 15  | 225 | 230,0 | 9,06  | 70 | 0,760 | 0,52  |
| 63,0  | 2 1/2" |    |    | 5   | 75  | 15  | 225 | 284,0 | 11,18 | 70 | 0,970 | 0,66  |
| 76,0  | 3"     |    |    | 5   | 75  | 15  | 225 | 342,0 | 13,46 | 70 | 1,330 | 0,90  |
| 90,0  | 3 1/2" |    |    | 4   | 60  | 12  | 180 | 405,0 | 15,94 | 70 | 1,800 | 1,21  |
| 102,0 | 4"     |    |    | 4   | 60  | 12  | 180 | 459,0 | 18,07 | 70 | 2,190 | 1,48  |
| 127,0 | 5"     |    |    | 3   | 45  | 9   | 135 | 597,0 | 23,50 | 50 | 2,900 | 1,95  |
| 152,0 | 6"     |    |    | 3   | 45  | 9   | 135 | 714,0 | 28,11 | 50 | 4,000 | 2,69  |
| 203,0 | 8"     |    |    | 2   | 30  | 6   | 90  | 954,0 | 37,56 | 40 | 6,200 | 4,17  |