

// 266LL

**Marine sanitary hose - PVC****Construction:** white thermoplastic elastomer.**Reinforcement:** white shock resistant rigid PVC.**Application:** sanitary hose for marine installations.**Constant operation:** -5 °C +60 °C (+23 °F +140 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
19,0	3/4"			8	120	24	350	75,0	2,95	70	0,300	0,21
25,0	1"			8	120	24	350	120,0	4,72	70	0,380	0,26
38,0	1 1/2"			6	90	18	270	170,0	6,69	70	0,580	0,39

// 202LL

**Marine sanitary hose 7 bar (100 psi)
ISO 8099****Tube:** white chlorobutyl - impermeable and odourless.**Reinforcement:** high tensile textile cords with embedded steel helix wire.**Cover:** white NBR/PVC - abrasion, ozone and hydrocarbon resistant.**Application:** sanitary hose for marine installations.

Designed for excellent kink resistance at tight bend radius and maximum flexibility.

Top permeability resistance.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
19,0	3/4"	29,00	1,14	7	100	21	300	38,0	1,50	100	0,670	0,46
25,0	1"	35,00	1,38	7	100	21	300	50,0	1,97	100	0,840	0,57
38,0	1 1/2"	48,00	1,89	7	100	21	300	76,0	2,99	100	1,260	0,85
51,0	2"	61,00	2,40	7	100	21	300	102,0	4,02	100	1,640	1,11