

// 722AA

**Sewage suction 5 bar (75 psi)**

Tube: black conductive NR - abrasion resistant.

Reinforcement: high tensile textile cords with embedded steel helix wire.

Cover: black conductive SBR/NR - abrasion and ozone resistant.

Application: cassette hose for sewer cleaning and waste suction vehicles.

Also suitable for bulk material suction and delivery.

Special construction for maximum flexibility.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
102,0	4"	118,00	4,65	5	75	15	225	408,0	16,06	90	4,600	3,10
127,0	5"	145,00	5,71	5	75	15	225	508,0	20,00	90	6,800	4,57
152,0	6"	172,00	6,77	5	75	15	225	608,0	23,94	90	8,600	5,78

// 268LL

**Pools-spa water circulation**

Construction: white PVC - abrasion and ozone resistant.

Reinforcement: white shock resistant rigid PVC.

Application: water circulation systems for pools and SPA.

Hose outside diameters made to fit rigid PVC pipe fittings.

Constant operation: -5 °C +60 °C (+23 °F +140 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
28,0	1 1/8"	32,00	1,26	6	90	18	270	168,0	6,61	90	0,250	0,17
32,0	1 1/4"	40,00	1,57	6	90	18	270	192,0	7,56	90	0,540	0,37
42,0	1 5/8"	50,00	1,97	6	90	18	270	252,0	9,92	90	0,780	0,53
55,0	2 1/6"	63,00	2,48	5	75	15	225	330,0	12,99	90	0,840	0,57

// 248AE

**High pressure water delivery 100 bar (1500 psi)
- Snow maker - Steel braided**

Tube: black SBR.

Reinforcement: high tensile steel wire braid.

Cover: blue CSM - abrasion and ozone resistant.

Application: high pressure water delivery.

Specially designed for artificial snow makers.

Designed for use of EN 853 1SN fittings.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
25,0	1"	36,00	1,42	100	1500	200	2900				0,980	0,66
38,0	1 1/2"	50,00	1,97	100	1500	200	2900				1,570	1,06