

Design and dimensions shown may be changed without prior notice

// 284AA

**Water delivery 10 bar (150 psi)****Tube:** black synthetic elastomer - oil mist resistant.**Reinforcement:** high tensile textile cords.**Cover:** black synthetic elastomer with longitudinal green stripes - abrasion and ozone resistant.**Application:** air and water delivery.**Constant operation:** -10 °C +60 °C (+14 °F +140 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
13,0	1/2"	19,00	0,75	10	150	30	450	104,0	4,09		0,205	0,14
16,0	5/8"	22,00	0,87	10	150	30	450	128,0	5,04		0,245	0,17
19,0	3/4"	26,00	1,02	10	150	30	450	152,0	5,98		0,345	0,24
25,0	1"	33,00	1,30	10	150	30	450	200,0	7,87		0,510	0,35
32,0	1 1/4"	44,00	1,73	7	100	21	300	256,0	10,08		0,950	0,64

// 284AH

**Water delivery 10 bar (150 psi)****Tube:** black synthetic elastomer - oil mist resistant.**Reinforcement:** high tensile textile cords.**Cover:** red synthetic elastomer - abrasion and ozone resistant.**Application:** air and water delivery.**Constant operation:** -10 °C +60 °C (+14 °F +140 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
13,0	1/2"	19,00	0,75	10	150	30	450	104,0	4,09		0,205	0,14
19,0	3/4"	26,00	1,02	10	150	30	450	152,0	5,98		0,345	0,24
25,0	1"	33,00	1,30	10	150	30	450	200,0	7,87		0,510	0,35