

Design and dimensions shown may be changed without prior notice

// 395BT



**Hot water wash down 40 bar (600 psi)
EU 10/2011 A+B+C**

Tube: grey non-toxic PVC.
Reinforcement: high tensile textile cords.
Cover: light blue synthetic elastomer - abrasion, ozone, animal fats and vegetable oils resistant.
Application: hot water wash down.
 Specially designed for the food and dairy industry.
 Designed for 40 bar at 70° C continuous use.
 240 bar minimum burst pressure at 20 °C.
 Food grade.
Constant operation: -10 °C +70 °C (+14 °F +158 °F)

↔		↔		↙		↘		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
12,0	15/32"	22,00	0,87	40	600	120	1750	84,0	3,31		0,340	0,23

// 351LL



Hot water wash down 10 bar (150 psi) - Built in nozzle

Tube: white EPDM.
Reinforcement: high tensile textile cords.
Cover: white EPDM - heat, abrasion and ozone resistant.
Application: hot and cold water wash down in paper mills and the food industry where a built in rubber nozzle is required to avoid floor and equipment damage.
Constant operation: -40 °C +120 °C (-40 °F +248 °F)

↔		↔		↙		↘		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
19,0	3/4"	31,00	1,22	10	150	40	600				0,630	0,43
25,0	1"	37,00	1,46	10	150	40	600				0,780	0,53
32,0	1 1/4"	46,00	1,81	10	150	40	600				1,140	0,77
38,0	1 1/2"	52,00	2,05	10	150	40	600				1,340	0,91

// 351LG



Hot water wash down 10 bar (150 psi) - Built in nozzle

Tube: white EPDM.
Reinforcement: high tensile textile cords.
Cover: green EPDM - heat, abrasion and ozone resistant.
Application: hot and cold water wash down in paper mills and the food industry where a built in rubber nozzle is required to avoid floor and equipment damage.
Constant operation: -40 °C +120 °C (-40 °F +248 °F)

↔		↔		↙		↘		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
19,0	3/4"	31,00	1,22	10	150	40	600				0,600	0,41
25,0	1"	37,00	1,46	10	150	40	600				0,740	0,50
32,0	1 1/4"	46,00	1,81	10	150	40	600				1,100	0,74
38,0	1 1/2"	52,00	2,05	10	150	40	600				1,290	0,87