

Design and dimensions shown may be changed without prior notice

// 4680H



**Liquid food S&D - PVC - Heavy duty**  
**FDA - EU 10/2011 A+B+C - AS 2070**

**Construction:** transparent PVC - abrasion and ozone resistant.  
**Reinforcement:** red shock resistant rigid PVC.

**Application:** liquid food and alcoholic beverages suction and delivery - max 20%.

Sterilize with 5% soda solution.

**Constant operation:** -5 °C +60 °C (+23 °F +140 °F)

↔		↔		↻		↻		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
25,0	1"			7	100	21	300	125,0	4,92	90	0,405	0,28
32,0	1 1/4"			7	100	21	300	160,0	6,30	90	0,530	0,36
38,0	1 1/2"			7	100	21	300	190,0	7,48	90	0,745	0,51
40,0	1 9/16"			7	100	21	300	200,0	7,87	90	0,765	0,52
51,0	2"			7	100	21	300	255,0	10,04	90	1,015	0,69
60,0	2 3/8"			7	100	21	300	300,0	11,81	90	1,475	1,00
63,0	2 1/2"			6	90	18	270	315,0	12,40	90	1,525	1,03
76,0	3"			5	75	15	225	380,0	14,96	90	1,930	1,30
80,0	3 1/8"			5	75	15	225	400,0	15,75	90	2,135	1,44
102,0	4"			4	60	12	180	510,0	20,08	90	3,355	2,26
120,0	4 3/4"			3	45	9	135	600,0	23,62	80	3,645	2,45

// 47200



**General purpose food quality S&D - PVC**  
**FDA - EU 10/2011 A+B+C - AS 2070**

**Construction:** transparent PVC - abrasion and ozone resistant.  
**Reinforcement:** steel helix wire.

**Application:** general purpose liquid food and alcoholic beverages suction and delivery - max 20%.

Sterilize with 5% soda solution.

**Constant operation:** -5 °C +60 °C (+23 °F +140 °F)

↔		↔		↻		↻		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
10,0	3/8"	16,00	0,63	15	225	45	650	40,0	1,57	90	0,160	0,11
13,0	1/2"	19,00	0,75	7	100	21	300	52,0	2,05	85	0,195	0,14
14,0	9/16"	20,00	0,79	6	90	18	270	56,0	2,20	85	0,210	0,15
16,0	5/8"	22,00	0,87	6	90	18	270	64,0	2,52	85	0,250	0,17
18,0	23/32"	25,00	0,98	6	90	18	270	72,0	2,83	85	0,300	0,21
20,0	13/16"	27,00	1,06	5	75	15	225	80,0	3,15	85	0,330	0,23
22,0	7/8"	29,00	1,14	5	75	15	225	88,0	3,46	85	0,380	0,26
25,0	1"	33,00	1,30	5	75	15	225	100,0	3,94	85	0,515	0,35
30,0	1 3/16"	38,00	1,50	4	60	12	180	120,0	4,72	85	0,610	0,41
32,0	1 1/4"	40,00	1,57	4	60	12	180	128,0	5,04	85	0,650	0,44
35,0	1 3/8"	44,00	1,73	4	60	12	180	140,0	5,51	85	0,785	0,53
38,0	1 1/2"	47,00	1,85	4	60	12	180	152,0	5,98	85	0,810	0,55
40,0	1 9/16"	49,00	1,93	3	45	9	135	160,0	6,30	85	0,885	0,60
45,0	1 3/4"	55,00	2,17	3	45	9	135	180,0	7,09	80	1,100	0,74
51,0	2"	61,00	2,40	3	45	9	135	204,0	8,03	80	1,230	0,83
60,0	2 3/8"	72,00	2,83	2	30	6	90	240,0	9,45	80	1,700	1,15
63,0	2 1/2"	75,00	2,95	2	30	6	90	252,0	9,92	80	1,775	1,20
70,0	2 3/4"	84,00	3,31	2	30	6	90	280,0	11,02	80	2,030	1,37
76,0	3"	90,00	3,54	2	30	6	90	304,0	11,97	70	2,350	1,58
80,0	3 1/8"	94,00	3,70	2	30	6	90	320,0	12,60	70	2,500	1,69
90,0	3 1/2"	104,00	4,09	2	30	6	90	360,0	14,17	70	3,000	2,02
102,0	4"	116,00	4,57	2	30	6	90	408,0	16,06	70	3,480	2,34
105,0	4 1/8"	121,00	4,76	3	45	9	135	420,0	16,54	90	4,250	2,86
152,0	6"	172,00	6,77	2	30	6	90	608,0	23,94	70	7,200	4,84