

Design and dimensions shown may be changed without prior notice

// 5190E


Acid-chemical S&D 16 bar (240 psi) - UPE - Corrugated
FDA - EU 10/2011 A+B+C+D2

Tube: transparent UPE (Ultra High Molecular Weight Polyethylene).

Reinforcement: high tensile textile cords with embedded steel helix wire.

Cover: blue EPDM - abrasion and ozone resistant.

Application: acid and chemical suction and delivery. Suitable for 98% of existing chemicals.

Special construction for maximum flexibility.

Constant operation: -30 °C +100 °C (-22 °F +212 °F) depending on conveyed chemical

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
51,0	2"			16	240	48	720	150,0	5,91	90	1,390	0,94
76,0	3"			16	240	48	720	228,0	8,98	90	2,510	1,69
102,0	4"			16	240	48	720	300,0	11,81	90	4,100	2,76

107

INDUSTRIAL HOSE

// 538AA


Tank cleaning 20 bar (300 psi) - EPDM - Textile braided

Tube: black conductive EPDM.

Reinforcement: high tensile textile braids - stainless steel antistatic wires.

Cover: black conductive EPDM - abrasion and ozone resistant.

Application: acid and chemical delivery in storage tanks cleaning applications.

Constant operation: -30 °C +100 °C (-22 °F +212 °F) depending on conveyed chemical

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
38,0	1 1/2"	54,00	2,13	20	300	60	900	304,0	11,97		1,330	0,90
51,0	2"	67,00	2,64	20	300	60	900	408,0	16,06		1,840	1,24