

## // 606AE

**Tank truck 10 bar (150 psi) - Corrugated - Low temperature**

**Tube:** black conductive NBR.

**Reinforcement:** high tensile textile cords with embedded steel helix wire.

**Cover:** blue CR - abrasion, ozone and hydrocarbon resistant.

**Application:** fuel, oil and hydraulic fluids suction and delivery. Specially designed for tank truck applications where extreme flexibility at low temperatures is required.

**Constant operation:** -54 °C +82 °C (-65 °F +180 °F)

| mm    | in | mm | in | bar | psi | bar | psi | mm    | in   | %   | kg/m  | lb/ft |  |
|-------|----|----|----|-----|-----|-----|-----|-------|------|-----|-------|-------|--|
| 51,0  | 2" |    |    | 10  | 150 | 30  | 450 | 76,0  | 2,99 | 100 | 1,540 | 1,04  |  |
| 76,0  | 3" |    |    | 10  | 150 | 30  | 450 | 114,0 | 4,49 | 100 | 2,680 | 1,81  |  |
| 102,0 | 4" |    |    | 10  | 150 | 30  | 450 | 153,0 | 6,02 | 100 | 3,910 | 2,63  |  |

## // 629AA

**Biofuel S&D 10 bar (150 psi)**

**Tube:** black conductive NBR.

**Reinforcement:** high tensile textile cords with embedded steel helix wire.

**Cover:** black CR - abrasion, ozone and hydrocarbon resistant.

**Application:** fuel and oil suction and delivery. Specially designed for biofuel and ethanol.

**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

| mm    | in     | mm     | in   | bar | psi | bar | psi | mm    | in    | %   | kg/m  | lb/ft |  |
|-------|--------|--------|------|-----|-----|-----|-----|-------|-------|-----|-------|-------|--|
| 19,0  | 3/4"   | 30,00  | 1,18 | 10  | 150 | 30  | 450 | 76,0  | 2,99  | 100 | 0,620 | 0,42  |  |
| 25,0  | 1"     | 36,00  | 1,42 | 10  | 150 | 30  | 450 | 100,0 | 3,94  | 100 | 0,770 | 0,52  |  |
| 32,0  | 1 1/4" | 43,00  | 1,69 | 10  | 150 | 30  | 450 | 128,0 | 5,04  | 100 | 0,970 | 0,66  |  |
| 38,0  | 1 1/2" | 49,00  | 1,93 | 10  | 150 | 30  | 450 | 152,0 | 5,98  | 100 | 1,200 | 0,81  |  |
| 51,0  | 2"     | 62,00  | 2,44 | 10  | 150 | 30  | 450 | 204,0 | 8,03  | 100 | 1,450 | 0,98  |  |
| 76,0  | 3"     | 89,00  | 3,50 | 10  | 150 | 30  | 450 | 304,0 | 11,97 | 90  | 2,540 | 1,71  |  |
| 102,0 | 4"     | 116,00 | 4,57 | 10  | 150 | 30  | 450 | 408,0 | 16,06 | 90  | 3,540 | 2,38  |  |