

// 60DAA

**Fuel-oil S&D 10 bar (150 psi)
EN 1765/S10****Tube:** black NBR.**Reinforcement:** high tensile textile cords with embedded steel helix wire.**Cover:** black CR- abrasion, ozone, sea water and hydrocarbon resistant.**Application:** crude oil and liquid petroleum products suction and delivery to/from tankers and bunkering vessels.
Max 55% aromatic content resistance.

Electrically continuous (discontinuous on request).

Built-in fittings.

Also available:

- 60EAA 100% aromatic content
- 60FAA biofuel

Constant operation: -20 °C +82 °C (-4 °F +180 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
100,0	4"			10	150	40	600	500,0	19,69	100	8,700	5,85	
150,0	6"			10	150	40	600	750,0	29,53	100	16,700	11,23	
200,0	8"			10	150	40	600	1000,0	39,37	100	25,500	17,14	
250,0	10"			10	150	40	600	1250,0	49,21	100	35,000	23,53	
300,0	12"			10	150	40	600	1500,0	59,06	100	51,800	34,82	

// 64AAA

**Fuel-oil delivery 10 bar (150 psi)
EN 1765/L10****Tube:** black NBR.**Reinforcement:** high tensile textile cords.**Cover:** black CR- abrasion, ozone, sea water and hydrocarbon resistant.**Application:** crude oil and liquid petroleum products delivery to/from tankers and bunkering vessels.

Max 55% aromatic content resistance.

Electrically continuous (discontinuous on request).

Built-in fittings.

Also available:

- 64BAA 100% aromatic content
- 64CAA biofuel

Constant operation: -20 °C +82 °C (-4 °F +180 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
100,0	4"			10	150	40	600	600,0	23,62		5,850	3,94	
150,0	6"			10	150	40	600	900,0	35,43		9,450	6,36	
200,0	8"			10	150	40	600	1200,0	47,24		14,100	9,48	
250,0	10"			10	150	40	600	1500,0	59,06		17,400	11,70	
300,0	12"			10	150	40	600	1800,0	70,87		24,550	16,50	