

Design and dimensions shown may be changed without prior notice

// 612AA



Nitro blast handling 20 bar (300 psi)

Tube: black conductive NBR - abrasion resistant.

Reinforcement: high tensile textile cords with embedded steel helix wire.

Cover: black conductive CR - abrasion, ozone, hydrocarbon and fire resistant.

Application: explosive handling in mobile delivery units. Specially designed for heavy duty reeling applications.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
51,0	2"	71,00	2,80	20	300	60	900	255,0	10,04	70	2,800	1,89
63,0	2 1/2"	83,00	3,27	20	300	60	900	315,0	12,40	70	2,980	2,01

// 964AA



Cable protection - FRAS AS 1802 - AS 2660

Tube: black conductive SBR/NR.

Reinforcement: high tensile textile cords.

Cover: black conductive SBR - abrasion, ozone and fire resistant.

Application: cable protection in underground mines. Also suitable for light duty air and water delivery max 5 bar (75 psi).

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
13,0	1/2"	21,00	0,83	5	75	15	225				0,240	0,17
16,0	5/8"	24,00	0,94	5	75	15	225				0,280	0,19
19,0	3/4"	29,00	1,14	5	75	15	225				0,410	0,28
25,0	1"	35,00	1,38	5	75	15	225				0,510	0,35
32,0	1 1/4"	42,00	1,65	5	75	15	225				0,630	0,43
38,0	1 1/2"	48,00	1,89	5	75	15	225				0,730	0,50
45,0	1 3/4"	55,00	2,17	5	75	15	225				0,850	0,58
51,0	2"	61,00	2,40	5	75	15	225				0,960	0,65