

Design and dimensions shown may be changed without prior notice

// 622AA



**Rig supply hard wall - Fuel-liquid mud**

**Tube:** black conductive NBR.

**Reinforcement:** high tensile textile cords with embedded steel helix wire - antistatic wire

**Cover:** black conductive CR - abrasion, ozone, hydrocarbon and fire resistant.

**Application:** fuel, oil and liquid mud transfer from supply vessels to offshore platforms.

Also suitable for sea water pumping and barite transfer.

Tensile end load resistance:

ID 3"      6.000 kg

ID ≥ 4"    10.000 kg

**ABS Type approved hose assemblies.**

Electrically continuous.

**Constant operation:** -30 °C +90 °C (-22 °F +194 °F)

| mm    | in | mm     | in   | bar | psi | bar | psi  | mm    | in    | %  | kg/m   | lb/ft |
|-------|----|--------|------|-----|-----|-----|------|-------|-------|----|--------|-------|
| 76,0  | 3" | 98,00  | 3,86 | 40  | 600 | 160 | 2320 | 380,0 | 14,96 | 90 | 4,870  | 3,28  |
| 102,0 | 4" | 128,00 | 5,04 | 40  | 600 | 160 | 2320 | 510,0 | 20,08 | 90 | 7,430  | 5,00  |
| 127,0 | 5" | 157,00 | 6,18 | 35  | 525 | 140 | 2000 | 635,0 | 25,00 | 90 | 11,150 | 7,50  |