

Design and dimensions shown may be changed without prior notice

// 680AA



Fuel-oil delivery 10 bar (150 psi)

Tube: black synthetic elastomer.

Reinforcement: high tensile textile cords - antistatic wire ID ≥ 13 mm.

Cover: black synthetic elastomer - abrasion, ozone and hydrocarbon resistant.

Application: general purpose fuel and oil delivery.

Constant operation: -10 °C +60 °C (+14 °F +140 °F)

↔		↔		↻		↻		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
6,0	1/4"	13,00	0,51	10	150	30	450	48,0	1,89		0,140	0,10
8,0	5/16"	15,00	0,59	10	150	30	450	64,0	2,52		0,170	0,12
10,0	3/8"	17,00	0,67	10	150	30	450	80,0	3,15		0,200	0,14
13,0	1/2"	20,00	0,79	10	150	30	450	104,0	4,09		0,245	0,17
19,0	3/4"	27,00	1,06	10	150	30	450	152,0	5,98		0,395	0,27
25,0	1"	35,00	1,38	10	150	30	450	200,0	7,87		0,625	0,43

// 654AA



EVOLUTION

**Multi-fuel 20 bar (300 psi)
SAE J30R7**

Tube: black conductive NBR.

Reinforcement: high tensile textile cords.

Cover: black conductive CR - abrasion, ozone and hydrocarbon resistant.

Application: fuel and oil delivery.

Also suitable for automotive and marine fuel transfer.

Constant operation: -40 °C +125 °C (-40 °F +257 °F)

↔		↔		↻		↻		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
6,0	1/4"	12,00	0,47	20	300	60	900				0,110	0,08
8,0	5/16"	14,00	0,55	20	300	60	900				0,130	0,09
10,0	3/8"	16,00	0,63	20	300	60	900				0,160	0,11
13,0	1/2"	20,00	0,79	20	300	60	900				0,220	0,15
16,0	5/8"	24,00	0,94	20	300	60	900				0,300	0,21
19,0	3/4"	27,00	1,06	20	300	60	900				0,330	0,23
25,0	1"	34,00	1,34	20	300	60	900				0,220	0,15