

// 687AA



**Automotive fuel 10 bar (150 psi)
DIN 73379/2A**

Tube: black NBR.
Reinforcement: high tensile textile cords.
Cover: black CR - abrasion, ozone and hydrocarbon resistant.
Application: petrol and diesel transfer in automotive applications. Also suitable for ecodiesel.
Constant operation: -35 °C +90 °C (-31 °F +194 °F)

↔		↔		↻		↻		⤴		⚠	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
3,5	9/64"	9,50	0,37	10	150	30	450	30,0	1,18		0,080	0,06
5,0	3/16"	11,00	0,43	10	150	30	450	55,0	2,17		0,100	0,07
5,5	7/32"	11,50	0,45	10	150	30	450	55,0	2,17		0,105	0,08
6,0	1/4"	12,00	0,47	10	150	30	450	60,0	2,36		0,115	0,08
7,5	19/64"	13,50	0,53	10	150	30	450	75,0	2,95		0,130	0,09
9,5	3/8"	15,50	0,61	10	150	30	450	85,0	3,35		0,160	0,11

// 689AA



Automotive fuel 10 bar (150 psi) - External textile braid

Tube: black NBR.
Reinforcement: high tensile textile braid.
Application: petrol and diesel transfer in automotive applications. Also suitable for unleaded fuel and ecodiesel.
Constant operation: -20 °C +100 °C (-4 °F +212 °F)

↔		↔		↻		↻		⤴		⚠	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
3,2	1/8"	7,00	0,28	10	150	30	450	25,0	0,98		0,040	0,03
3,5	9/64"	7,50	0,30	10	150	30	450	28,0	1,10		0,045	0,04
4,0	5/32"	8,00	0,31	10	150	30	450	35,0	1,38		0,050	0,04
4,5	11/64"	9,50	0,37	10	150	30	450	38,0	1,50		0,060	0,05
5,0	3/16"	10,00	0,39	10	150	30	450	40,0	1,57		0,065	0,05
5,5	7/32"	10,50	0,41	10	150	30	450	45,0	1,77		0,070	0,05
6,0	1/4"	11,00	0,43	10	150	30	450	50,0	1,97		0,075	0,06
7,5	19/64"	12,50	0,49	10	150	30	450	60,0	2,36		0,085	0,06
8,0	5/16"	13,00	0,51	10	150	30	450	65,0	2,56		0,090	0,07
9,0	23/64"	14,00	0,55	10	150	30	450	75,0	2,95		0,105	0,08
10,0	3/8"	15,00	0,59	10	150	30	450	80,0	3,15		0,110	0,08
12,0	15/32"	17,00	0,67	8	120	24	350	90,0	3,54		0,135	0,10

// 688AA



Diesel oil delivery 15 bar (225 psi) - External steel braid

Tube: black NBR.
Reinforcement: plated steel braid.
Application: diesel oil delivery. Specially designed for burner feed line.
Constant operation: -20 °C +100 °C (-4 °F +212 °F)

↔		↔		↻		↻		⤴		⚠	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
6,0	1/4"	11,00	0,43	15	225	70	1000	30,0	1,18		0,100	0,07
8,0	5/16"	13,00	0,51	15	225	70	1000	40,0	1,57		0,155	0,11
10,0	3/8"	15,00	0,59	15	225	70	1000	45,0	1,77		0,190	0,13
12,0	15/32"	17,00	0,67	15	225	70	1000	55,0	2,17		0,230	0,16