

// 7640L

**Plaster conveyance - Polyurethane**

Construction: transparent polyurethane - abrasion and ozone resistant.

Reinforcement: white shock resistant rigid PVC.

Application: pneumatic conveyance of pre-mixed synthetic plaster from silo to plaster pumping machine. Assembly complete with fittings also available.

Constant operation: -20 °C +60 °C (-4 °F +140 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
45,0	1 3/4"							203,0	7,99	60	0,680	0,46

// 752AA

**Plaster 10 bar (150 psi)**

Tube: black conductive NR - abrasion resistant.

Reinforcement: high tensile textile cords.

Cover: black SBR/NR - abrasion and ozone resistant - pin pricked.

Application: plaster and sand/cement mix pumping. Also suitable for heavy duty sandblast.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
60,0	2 3/8"	80,00	3,15	10	150	30	450				2,310	1,56
65,0	2 9/16"	85,00	3,35	10	150	30	450				2,520	1,70
90,0	3 1/2"	113,00	4,45	10	150	30	450				4,110	2,77
102,0	4"	127,00	5,00	10	150	30	450				4,680	3,15

// 757AA

**Plaster 40 bar (600 psi)**

Tube: black conductive NR - abrasion resistant.

Reinforcement: high tensile textile cords.

Cover: black SBR/NR - abrasion and ozone resistant.

Application: plaster pumping.

Constant operation: -30 °C +80 °C (-22 °F +176 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
25,0	1"	38,00	1,50	40	600	100	1500				0,700	0,48
32,0	1 1/4"	46,00	1,81	40	600	100	1500				0,870	0,59
35,0	1 3/8"	49,00	1,93	40	600	100	1500				0,960	0,65
38,0	1 1/2"	54,00	2,13	40	600	100	1500				1,190	0,80
51,0	2"	67,00	2,64	40	600	100	1500				1,600	1,08