

Design and dimensions shown may be changed without prior notice

// 754AA

**Concrete vibrator 10 bar (150 psi)****Tube:** black SBR.**Reinforcement:** high tensile textile cords.**Cover:** black SBR - abrasion and ozone resistant.**Application:** pneumatic concrete vibrators.**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
19,0	3/4"	31,00	1,22	10	150	40	600				0,690	0,47	
25,0	1"	39,00	1,54	10	150	40	600				1,030	0,70	

// 737AA

**Concrete pumping 40 bar (600 psi)****Tube:** black conductive NR - abrasion resistant.**Reinforcement:** high tensile textile cords.**Cover:** black conductive SBR/NR - abrasion and ozone resistant.**Application:** concrete pumping.**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
51,0	2"	69,00	2,72	40	600	100	1500				1,810	1,22	
63,0	2 1/2"	83,00	3,27	40	600	100	1500				2,500	1,69	
76,0	3"	104,00	4,09	40	600	100	1500				4,330	2,91	
90,0	3 1/2"	118,00	4,65	40	600	100	1500				5,080	3,42	
102,0	4"	130,00	5,12	40	600	100	1500				5,750	3,87	