

Design and dimensions shown may be changed without prior notice

// 756AA

**Gunite 14 bar (200 psi) - FRAS
exceeds AS 2660/C****Tube:** black conductive NR - abrasion resistant.**Reinforcement:** high tensile textile cords.**Cover:** black conductive SBR - abrasion, ozone and fire resistant.**Application:** gunite.**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
38,0	1 1/2"	62,00	2,44	14	200	56	800				2,200	1,48
51,0	2"	75,00	2,95	14	200	56	800				2,810	1,89

// 765AA

**Stone dust 7 bar (100 psi) - FRAS
exceeds AS 2660/C****Tube:** black conductive SBR/NR - abrasion resistant.**Reinforcement:** high tensile textile cords.**Cover:** black conductive SBR - abrasion, ozone and fire resistant.**Application:** "Stone dusting" in underground mines.
Also suitable for air and water delivery.**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
32,0	1 1/4"	46,00	1,81	7	100	28	400				1,010	0,68
51,0	2"	65,00	2,56	7	100	28	400				1,510	1,02