

## // 760LA

**Bulk food delivery 5 bar (75 psi)  
FDA****Tube:** white NR - abrasion resistant.**Reinforcement:** high tensile textile cords - antistatic wire.**Cover:** black conductive SBR/NR - abrasion and ozone resistant.**Application:** bulk food and material delivery.

Specially designed for grain, flour and plastic pellets transfer.

**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

| mm    | in      | mm     | in   | bar | psi | bar | psi | mm | in | % | kg/m  | lb/ft |  |
|-------|---------|--------|------|-----|-----|-----|-----|----|----|---|-------|-------|--|
| 75,0  | 3"      | 93,00  | 3,66 | 5   | 75  | 15  | 225 |    |    |   | 2,370 | 1,60  |  |
| 90,0  | 3 1/2"  | 102,00 | 4,02 | 5   | 75  | 15  | 225 |    |    |   | 2,120 | 1,43  |  |
| 100,0 | 4"      | 120,00 | 4,72 | 5   | 75  | 15  | 225 |    |    |   | 3,550 | 2,39  |  |
| 102,0 | 4"      | 120,00 | 4,72 | 5   | 75  | 15  | 225 |    |    |   | 3,170 | 2,14  |  |
| 110,0 | 4 5/16" | 122,00 | 4,80 | 5   | 75  | 15  | 225 |    |    |   | 2,540 | 1,71  |  |

## // 760LB

**Bulk food delivery 5 bar (75 psi)  
FDA****Tube:** white NR - abrasion resistant.**Reinforcement:** high tensile textile cords - antistatic wire.**Cover:** grey SBR/EPDM - abrasion and ozone resistant.**Application:** bulk food and material delivery.

Specially designed for grain, flour and plastic pellets transfer.

**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

| mm    | in | mm     | in   | bar | psi | bar | psi | mm | in | % | kg/m  | lb/ft |  |
|-------|----|--------|------|-----|-----|-----|-----|----|----|---|-------|-------|--|
| 102,0 | 4" | 118,00 | 4,65 | 5   | 75  | 15  | 225 |    |    |   | 3,140 | 2,12  |  |