

// 767AL

**Bulk material S&D - PVC - Polyurethane lined**

Construction: black antistatic polyurethane coextruded with black PVC - abrasion and ozone resistant.

Reinforcement: white shock resistant rigid PVC.

Application: bulk material suction and low pressure delivery-gravity feed.

Specially designed for gravel, cement and iron ore transfer.

Constant operation: -20 °C +60 °C (-4 °F +140 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
51,0	2"			3	45	9	135	102,0	4,02	90	0,900	0,61
63,0	2 1/2"			3	45	9	135	126,0	4,96	90	1,470	0,99
76,0	3"			3	45	9	135	152,0	5,98	90	1,830	1,23
102,0	4"			2	30	6	90	204,0	8,03	90	2,980	2,01
127,0	5"			2	30	6	90	254,0	10,00	90	4,200	2,83
152,0	6"			2	30	6	90	304,0	11,97	90	5,150	3,47

// 780AA

**Bulk material S&D - PVC**

Construction: black antistatic synthetic elastomer.

Reinforcement: black shock resistant thermoplastic elastomer.

Application: bulk material suction and low pressure delivery-gravity feed.

Specially designed for gravel, cement and iron ore transfer.

Constant operation: -15 °C +60 °C (+5 °F +140 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
38,0	1 1/2"	47,00	1,85	2	30	8	120	80,0	3,15	100	0,570	0,39
51,0	2"	61,00	2,40	2	30	8	120	120,0	4,72	100	0,860	0,58
63,0	2 1/2"	75,00	2,95	2	30	8	120	200,0	7,87	100	1,090	0,74
76,0	3"	90,00	3,54	1	15	4	60	240,0	9,45	100	1,390	0,94
102,0	4"	119,00	4,69	1	15	4	60	320,0	12,60	100	2,560	1,73
127,0	5"	146,00	5,75	1	15	4	60	480,0	18,90	100	3,320	2,24
152,0	6"	175,00	6,89	1	15	4	60	720,0	28,35	100	4,890	3,29