

Design and dimensions shown may be changed without prior notice

// 776AA



**Mineral sampling 35 bar (525 psi)**

**Tube:** black conductive NR - abrasion resistant.

**Reinforcement:** high tensile textile cords with embedded steel helix wire.

**Cover:** black conductive SBR/NR - abrasion and ozone resistant.

**Application:** mineral recovery in sampling operations.

**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
51,0	2"	77,00	3,03	35	525	105	1530	204,0	8,03	100	3,000	2,02
76,0	3"	106,00	4,17	35	525	105	1530	304,0	11,97	90	4,950	3,33
102,0	4"	134,00	5,28	35	525	105	1530	408,0	16,06	90	7,320	4,92

// 776HA



**Mineral sampling 35 bar (525 psi)**

**Tube:** red NR - abrasion resistant.

**Reinforcement:** high tensile textile cords with embedded steel helix wire.

**Cover:** black conductive SBR/NR - abrasion and ozone resistant.

**Application:** mineral recovery in sampling operations.

**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
76,0	3"	106,00	4,17	35	525	105	1530	304,0	11,97	90	4,890	3,29