

// 902AA

**Hot air blower 10 bar (150 psi) - Hard wall**

Tube: black EPDM - heat resistant.

Reinforcement: high tensile textile cords with embedded steel helix wire.

Cover: black EPDM - heat, abrasion and ozone resistant.

Application: hot air connection from volumetric compressor to bulk food/material road tanker.

Special light weight and flexible construction.

Constant operation: -40 °C +180 °C (-40 °F +356 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
51,0	2"	63,00	2,48	10	150	30	450	153,0	6,02	100	1,510	1,02	
63,0	2 1/2"	77,00	3,03	10	150	30	450	189,0	7,44	100	2,000	1,35	
76,0	3"	90,00	3,54	10	150	30	450	228,0	8,98	90	2,400	1,62	
102,0	4"	116,00	4,57	10	150	30	450	306,0	12,05	90	3,330	2,24	

// 902AE

**Hot air blower 10 bar (150 psi) - Hard wall**

Tube: black EPDM - heat resistant.

Reinforcement: high tensile textile cords with embedded steel helix wire.

Cover: blue EPDM - heat, abrasion and ozone resistant.

Application: hot air connection from volumetric compressor to bulk food/material road tanker.

Special light weight and flexible construction.

Constant operation: -40 °C +180 °C (-40 °F +356 °F)

mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
76,0	3"	90,00	3,54	10	150	30	450	228,0	8,98	90	2,310	1,56	