

Design and dimensions shown may be changed without prior notice

// 952AA



Hot air blower 10 bar (150 psi) - Soft wall - External textile braid

Tube: black EPDM - heat resistant.
Reinforcement: high tensile textile braids.
Application: hot air connection from volumetric compressor to bulk food/material road tanker.
Constant operation: -40 °C +180 °C (-40 °F +356 °F)

												
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
51,0	2"	67,00	2,64	10	150	30	450	255,0	10,04		1,580	1,07
76,0	3"	92,00	3,62	10	150	30	450	380,0	14,96		2,340	1,58

// 962LA



Hot air blower 10 bar (150 psi) - Soft wall

Tube: white EPDM - heat resistant.
Reinforcement: high tensile textile cords.
Cover: black EPDM - heat, abrasion and ozone resistant.
Application: hot air connection from volumetric compressor to bulk food/material road tanker.
Constant operation: -40 °C +180 °C (-40 °F +356 °F)

												
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
51,0	2"	69,00	2,72	10	150	30	450	306,0	12,05		2,580	1,74
76,0	3"	94,00	3,70	10	150	30	450	456,0	17,95		3,490	2,35