

Design and dimensions shown may be changed without prior notice

// DRILLING

// FLEXOR RIG - SLIM HOLE ROTARY



MSHA

Tube: oil resistant synthetic rubber and biodegradable hydraulic fluid.

Reinforcement: four high tensile steel spirals.

Cover: abrasion, ozone and hydrocarbon resistant synthetic rubber.

Application: Rotary hose, specially designed for portable, workover and seismograph drilling rigs.

Temperature: -40 °C +121 °C (-40 °F +250 °F)

Length: 61 m (200 ft)

Notes: four spirals construction. Available with male API threaded extra-long hexagon fittings.

ID (mm)	ID (in)	OD (mm)	OD (in)	WP (bar)	WP (psi)	BP (Mpa)	BP (psi)	BR (mm)	BR (in)	Weight (kg/m)	Weight (lb/ft)
63,0	2 1/2"	79,0	3,11	220	3200	56,0	8000	720	28,35	4,897	3,30
76,0	3"	92,5	3,64	220	3200	56,0	8000	840	33,07	5,760	3,88

// FLEXOR RIG - ROTARY



MSHA

Tube: oil resistant synthetic rubber and biodegradable hydraulic fluids.

Reinforcement: six high tensile steel spirals.

Cover: abrasion, ozone and hydrocarbon resistant synthetic rubber.

Application: Rotary hose, specially designed for portable, workover and seismograph drilling rigs.

Temperature: -40 °C +121 °C (-40 °F +250 °F)

Length: 61 m (200 ft)

Notes: six spirals construction. Available with male API threaded extra-long hexagon fittings.

ID (Dash)	ID (mm)	ID (in)	OD (mm)	OD (in)	WP (Mpa)	WP (psi)	BP (Mpa)	BP (psi)	BR (mm)	BR (in)	Weight (kg/m)	Weight (lb/ft)
48	76,0	3"	95,6	3,76	35,0	5000	87,5	12500	900	35,43	7,917	5,33